REFRACTORY MATERIALS

A SERIES OF MONOGRAPHS

VOLUME 3

CONTENTS

	PRE	FACE	
	LIST	OF FIGURES	
	LIST	TOF TABLES	
I.	INT	RODUCTION	
II.	FIB	ER-COMPOSITE TECHNOLOGY 5	,
III.	REI	INFORCEMENTS	
	Α.	Introduction	
	B.	Characterization of the Newer Reinforcements 12	2
	C.	Reinforcement Preparation	2
		1. Melt drawing	;
		2. Conventional wire drawing	;
		3. Bundle drawing	;
		4. Taylor process	5
		$5. Extrusion \dots 16$)
		6. Rayon spinnerette)
		7. Precursor conversion \ldots \ldots \ldots \ldots 16	
		8. Chemical vapor deposition	5
	D.	Reinforcement Properties	3
	E.	Applications	3
IV.	TES	STING FINE FILAMENTS AND WHISKERS 27 (By R. L. Mehan)	7
	Α.	Introduction	7
	B.	Tensile Tests	3
		1. Fiber testing	l
		2. Whisker testing	5
	C.	Bend Tests	l
	D.	Dynamic Methods for Determining Elastic Constants 47	7
		1. Torsion pendulum	7
		2 Resonance or vibrating reed technique 4'	7

C	n	N	T	F	N	T	S
C	v	14		-	14		0

		 Standing wave technique	.7
V.	FIBI	ER-COMPOSITE MATERIALS 4	9
	Α.	Characterization41. Fiber length42. Fiber concentration53. Fiber diameter54. Fiber orientation55. Fiber shape56. Constituent behavior57. Constituent composition5	19 19 19 19 19 19 19 19 19 19 19 19 19 1
	B.	Mechanics and Interfaces	57
	C.	Resin-Matrix Composites	58
	D.	Metal-Matrix Composites 7 1. Fabrication 7 2. Properties 7 3. Applications 7	71 79 79
	E.	Ceramic-Matrix Composites)1
VI.	EVA	LUATION AND CONCLUSIONS)3
VII.	RES	ULTS OF VISITS AND QUESTIONNAIRES 10)9
	A.	Introduction)9
	B.	Contact Reports	16
VIII.	PAT	ENT ABSTRACTS	51
	A.	Introduction	51
	B.	Index to Patent Abstracts	52
	C.	Patent Abstracts	59
IX.	BIB	LIOGRAPHY	55
	A.	Introduction	55
	B.	References by Author	57
Х.	SUP	PLEMENTARY INFORMATION 43	32
	SUB.	JECT INDEX	34

viii

1.	Interest in fiber and fiber-reinforced materials based upon the number of publications listed in the Bibliography and in Ref. 475	2
2.	Potential specific strength and specific modulus of conven- tional alloys and advanced fiber-reinforced composites at room temperature	7
3.	Scope of fiber-composite technology	8
4.	Role of the constituents in fiber-composite materials	10
5.	Characterization of reinforcements according to morphology	13
6.	Comparison of the cross-sectional dimensions for various fiber reinforcements (from Ref. 702)	14
7.	Flow chart of rayon yarn production (Courtesy of Food Machinery Corp.).	17
8.	Effect of forming process on the strength of various fibers	22
9.	Room temperature specific strength and specific stiffness of several fibers	25
10.	Elevated temperature strength of several fibers	25
11.	Cross-section (unetched) and surface appearance of a fractured boron/tungsten filament (600X)	29
12.	Photomicrographs of alumina whiskers showing complex cross sections and oblique fracture (Ref. 579)	30
13.	Effect of gage length on the elastic modulus of steel and tungsten wire. Data obtained from an Instron machine using	
	aluminum-lined air grips (80 psi), a rigid coupling system, and a "C" load cell	33
14.	View of a boron filament held between Instron-type air grips during a tensile test	35
15.	Marsh machine with Thornel-25 fiber mounted ready for	
	test	- 38

16.	Schematic sketch of Air Force Materials Laboratory micro- tensile testing machine (Courtesy of Herzog, Ref. 311)	39
17.	Fiber tensile testing fixture (Courtesy of Kelsey and Krock, Ref. 380)	40
18A.	Compilation of strength of Al_2O_3 whiskers as a function of cross-sectional area (Ref. 494)	42
18B.	Strength of metal-coated Al_2O_3 whiskers extracted from an aluminum matrix (Ref. 494)	43
19.	Deviation from simple theory for maximum bending deflection of high-strength, high-modulus fibers (Courtesy of Jour. American Ceramic Society. Ref. 492)	44
20.	Photomicrographs of bent Al_2O_3 whiskers used to evaluate whisker stress	46
21.	Relationship of composite tensile strength to fiber aspect ratio, and to fiber volume fraction	50
22.	Strength of carefully selected alumina whiskers as a function of size (from Regester, Ref. 579)	54
23.	Effect of fiber orientation on the uniaxial tensile strength of fiber-composite material (from Kelly and Davies, Ref. 374)	56
24.	Interfacial shear stress and fiber tensile stress of an elastic fiber in an elastic matrix	61
25.	Wetting of Al_2O_3 substrates by molten aluminum. In A and B, the Al_2O_3 was uncoated; in C and D, the Al_2O_3 was coated with an adherent film of nickel (from Mehan, et al., Ref. 493)	62
26.	Strength of silver composites containing Ni-coated and un- coated Al_2O_3 whiskers (from Sutton, Ref. 705)	63
27.	Effect of fiber strength and fiber volume fraction on composite tensile strength	64
28.	Tensile stress-strain relationships for the matrix, fiber, and composite material	66
29.	Hollow ring-stiffened cylinder of boron-filament epoxy construction (from Saffire, Ref. 611)	72
30.	Strength retention at various temperatures of pure aluminum and aluminum strengthened with Al_2O_3 particles and with fused silica fibers (from Sutton and Chorné, Ref. 708)	81
31.	Strength retention at various temperatures of pure silver strengthened with Al_2O_3 particles and whiskers (from Sutton and Chorné, Ref. 708)	82

х

32.	Effect of fiber volume fraction on the tensile strength of metal-matrix composites reinforced with continuous, parallel fibers (from Sutton, Ref. 702)	83
33.	Effect of fiber volume fraction on the tensile strength of metal-matrix composites reinforced with discontinuous, parallel fibers (from Sutton, Ref. 702)	84
34.	Effect of fiber volume fraction on the modulus of Ti-6Al-4V alloy at various temperatures (from Jech, et al., Courtesy of Interscience Pub., Ref. 356)	86
35.	Creep strain of Inconel 600 reinforced with different volume fractions of tungsten fibers (from Ellison and Harris, Courtesy of Appl. Materials Res., Ref. 209)	87
36.	Ultimate tensile strength of boron-filament aluminum composites as a function of filament volume fraction (Courtesy of United Aircraft Research Laboratories, AF Contract No. AF33(615)-3209, Contact Rept. No. 87).	91
37.	Strength-to-density ratio as a function of temperature for specimens of plasma-sprayed boron-filament reinforced aluminum and other alloys (Courtesy of United Aircraft Research Laboratories, Contact Rept. No. 87)	92
38.	Photomicrograph of a transverse section of a composite of aluminum containing $B_4C/tungsten$ core filaments. Specimen was prepared by infiltrating molten aluminum into 84 v/o of B_4C filaments	93
39.	Composite specimen of aluminum reinforced with 30 v/o of Al_2O_3 whiskers. At one end, the aluminum was dissolved to expose the whiskers.	94
40.	Transverse section of aluminum matrix composite specimen containing 27 v/o of Al_2O_3 whiskers	95
41.	Whisker-reinforced nickel sheet which was fabricated by electro-depositing nickel into a mat of Ni-coated Al_2O_3 whiskers (Ref. 151)	97
42.	Strength dependence on temperature for various metal- matrix composites	98
43.	Turbine blade configuration cast directly by unidirectional solidification of Al-Al ₃ Ni eutectic alloy (Courtesy of United Aircraft Research Lab., Contact Rept. No. 87) $\dots \dots \dots$	100
44A	. Hot-formed carbon-fabric aluminum composite (Courtesy of Aeronutronic Division, Ford Motor Co.)	118

xi

LIST	OF	FIGUI	RES

44B.	Cross-section of Thornel 25 fibers in 2024 aluminum matrix (Courtesy of Aeronutronic Division, Ford	110
	Motor Co	118
45.	Specimens fabricated using 3-D weave process (Courtesy of AVCO Corp.)	128
46.	Structure of boron-fiber reinforced titanium formed by gas pressure bonding (Courtesy of Battelle Memorial Institute) .	135
47.	Boron-fiber reinforced titanium formed by explosive com- paction (Courtesy of Battelle Memorial Institute)	135
48.	Nickel - 60 v/o WDF graphite felt (Courtesy of Battelle Memorial Institute)	136
49.	Nickel - 77 v/o Thornel graphite yarn (Courtesy of Battelle Memorial Institute).	136
50.	Effect of growth direction on Al_2O_3 whisker strength (Courtesy of CFTH)	150
51.	Hollow, hexagonal cross-sections of glass microtape reinforced resin (Courtesy of DeBell & Richardson, Inc.)	153
52.	Various composites made with hollow, hexagonal cross-section microtapes (Courtesy of DeBell & Richardson, Inc.)	154
53.	Boron-fiber reinforced F-111 tail section (Courtesy of General Dynamics Corp.)	161
54.	Microstructure of epoxy reinforced by Al_2O_3 whiskers	167
55A.	Nickel - 10 v/o quartz fiber; tapes and wires (Courtesy of Hittman Associates, Inc.)	185
55B.	Cobalt -10 v/o quartz fiber; cone and nozzle (Courtesy of Hittman Associates, Inc.)	185
56.	Cobalt-quartz fiber composite (64X) (Courtesy of Hittman Associates, Inc.)	186
57.	Deformation pattern in a silver matrix containing a single 5-mil diameter, 20-mil long tungsten fiber (Courtesy of IITRI)	190
58.	Strain hardening in the silver matrix along a 60-mil long tungsten fiber (Courtesy of IITRI)	191
59.	Length distribution of Al ₂ O ₃ whiskers (Courtesy of P. R. Mallory & Co., Inc.)	196
60.	Strength of Al_2O_3 whiskers as a function of cross-sectional area (Courtesy of P. R. Mallory & Co., Inc.)	197

xii

3	
•	
,	

)6

)7

61.	Microstructure of experimental aluminum-copper alloy as cast in machined graphite molds. Note appearance of 10-30 micron diameter aluminum oxide fibers at the grain bound- aries (680X) (Courtesy of Mitron R & D Corp.)	20
62.	Schematic of Rolls-Royce process for simultaneous drawing and metallizing SiO_2 fiber (Courtesy of Rolls-Royce, Ltd.).	22
63.	Comparison of ultimate tensile strength of silica fiber-rein- forced aluminum with various other aluminum alloys (Courtesy of Rolls-Royce, Ltd.)	22
64.	Comparison of bending fatigue strength of silica fiber-rein- forced aluminum and a widely used aluminum alloy (Courtesy of Rolls-Royce, Ltd.)	22
65.	Stress-rupture properties at various temperatures for silica fiber-reinforced aluminum (courtesy of Rolls-Royce, Ltd.)	22
66.	Anisotropy of Al-Al ₃ Ni composite demonstrated by tensile strength measurements parallel to and at various angles to whisker alignment (Courtesy of United Aircraft Corp.)	23
67.	Creep behavior of Al-Al ₃ Ni at 250°C, 15,000 psi (Courtesy of United Aircraft Corp.) \ldots	24
68.	Effect of temperature on the tensile strength and ductility of unidirectionally solidified $Al-Al_3Ni$ and $Al-CuAl_2$ (Courtesy of United Aircraft Corp.).	24
69.	Microstructure of Ta-Ta ₂ C alloy (A65-067) unidirectionally solidified two times (Courtesy of United Aircraft Corp.)	24
70.	Effect of temperature on the tensile properties of Ta-10W and unidirectionally solidified Ta-Ta ₂ C (Courtesy of United Aircraft Corp.).	24
71.	Effect of reinforcement shape on mechanical properties of unidirectionally solidified composites (Courtesy of United Aircraft Corp.).	24
72.	Whiskers of β -rhombohedral boron (4X) (Courtesy of Watervliet Arsenal)	25
73A.	Iron whiskers grown in magnetic field (3 kilo-oersteds) on a nonmagnetic spiral placed in a boat (Courtesy of Watervliet Arsenal)	25
73B.	Close-up view of iron whiskers in the boat, showing alignment and absence of over-growth (Courtesy of	25
	waterviet Arsenal)	23

x

74.	Variation of yield and ultimate tensile strengths of copper matrix composites, reinforced by continuous tantalum filaments (Courtesy of Watervliet Arsenal)	259
75.	Electroformed composite of α -Al ₂ O ₃ whiskers in nickel (Courtesy of Watervliet Arsenal)	260

xiv